

Coolant



### PETRONAS Tutela Coolant LL-Si Premix

Range:

**Long description:** Premium performance ready to use Long-Life Coolant delivering optimized performance and component durability for vehicles cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Silicate Organic Acid inhibitor (Si-OAT Technology), free of nitrites, borates, phosphates and amines, it provides excellent protection against overheating, frost and corrosion, especially for the cooling systems that contain innovative light alloy materials. Suitable for Europeans, Americans and Asian passenger cars and commercial vehicles, including hybrid electrified applications

[Product data sheet](#) [Safety data sheet](#)

**Industry Specifications:** AS 2108-2004 ASTM D 3306 ASTM D 4985 ASTM D 6210 BS 6580:2010 CUNA NC 956-16 GB 29743-2013 JIS K 2234:2006 ONORM V 5123 SAE J1034 SANS 1251:2005

**OEM Performance - Only for Automotive:** Cummins CES 14603 Deutz DQC CC-14 Daimler/Mercedes-Benz 325.5 and 325.6 IRIZAR, S. COOP from Sep. 2016 Liebherr Minimum LH-01-COL3A MAN 324 Type Si-OAT MTU MTL 5048 Porsche from MY 1996 VW / Audi / Seat / Skoda / Lamborghini / Bentley / Bugatti - TL 774-G

**Application(s) - For Consumers pages:** Light-duty Commercial Vehicle (LCV), Passenger car, Heavy-Duty Vehicle (HD)